

# RAPID ROLL DOOR



Eurocold



## DURABLE FULLY ENGINEERED RAPID ROLL DOOR, DESIGNED FOR INTERIOR AMBIENT, CHILL AND FREEZER APPLICATIONS

### Frame

- Anodised aluminium guides with nylon brush seals and stainless steel components
- Guides complete with nylon brush seals

### Anti-crash

- Auto-repairs in case canvas and/or reinforcements come out of the lateral guides

### Door leaf

- Robust construction high resistance polyester door leaf
- Maximum clear opening height 4.5m and width 4m
- Electronically controlled movement
- Triphasic motor with electronic braking system
- Operation speeds of 1m per second
- Integrated photo cell
- Low noise gear assembly
- Internal and external push button operation
- M2 non-flammable coated on PVC colour - Variety of colours available

### Additional options available

- Radar, pull cord, magnetic loop, remote control and safety light



MEMBER OF THE FEDERATION OF SMALL BUSINESSES



Certificate No. GB260 012



Registration No. 0044/1

SALES HOTLINE - 0845 094 4060

# RAPID FOLD-UP DOOR



Eurocold



**DURABLE FULLY ENGINEERED RAPID FOLD-UP DOOR, DESIGNED FOR AREAS WITH LARGE ACCESS DIMENSIONS**

#### Frame

- ☺ Anodised aluminium guides with nylon brush seals and stainless steel components
- ☺ Guide with integrated photoelectric cell

#### Door leaf

- ☺ High resistance polyester door leaf
- ☺ Wind-resistant (class 3 rating) reduces draughts and minimising temperature loss
- ☺ M2 non-flammable coated on PVC colour - variety of colours available
- ☺ Safety edge
- ☺ Maximum clear opening height 6.5m and width 6m

#### Features

- ☺ Digital door position control
- ☺ Motorised rapid fold-up door approx. 0.6m/s
- ☺ Suitable for both interior and exterior
- ☺ Low noise gear assembly
- ☺ Facilitates traffic flow
- ☺ Electronic end-of-travel sensors
- ☺ Safety breaking mechanism
- ☺ Exterior and interior emergency stop buttons



**SALES HOTLINE - 0845 094 4060**